



## CRANE SPECIFICATION

# TADANO TR250M

## COMPREHENSIVE LIFTING SOLUTIONS

We look forward to providing a full heavy lift engineering and crane solution for your next project. Our heavy lift engineers and on site personnel are experienced in managing and organising highly de-manding lift requirements.

Contact us to discuss your lifting requirements and a free quote.

### BRISBANE (HQ)

07 3907 5800  
37 Paringa Rd, Murarrie, QLD, 4172

### ROMA

07 4622 5522  
8 Wormwell Drive, Roma QLD 4455

### BALLINA

02 6686 7748  
5 Convair Ave, Ballina, NSW, 2478

### SUNSHINE COAST

0409 595 618  
562 Maroochydore Rd, Kunda Park, QLD, 4556

### GLADSTONE

07 4972 9326  
7 Red Cover Rd, Gladstone, QLD, 4680

### TOWNSVILLE

07 4779 4088  
16 Mackley St, Garbutt QLD 4814

### ROCKHAMPTON

07 4939 1095  
371 Leichhardt St, Rockhampton QLD, 4700

### MACKAY

07 4952 6998  
135 Diesel Drive, Paget QLD 4740

### GOLD COAST

07 5593 4688  
9 Kimberley Rd, Burleigh Heads, QLD, 4220



# ROUGH TERRAIN CRANE

## TR-250M

### *JAPANESE SPECIFICATIONS*

**TR**

OUTLINE	SPEC. NO.
4-section Boom, 2-staged Power Tilt Jib X-type Outrigger	TR-250M-7-00101

Control No. JA-01

# TR-250M

## CRANE SPECIFICATIONS

### CRANE CAPACITY

9.5m	Boom	25,000kg	at 3.5m	( 8part-line)
16.5m	Boom	19,000kg	at 4.0m	( 6part-line)
23.5m	Boom	12,500kg	at 5.0m	( 4part-line)
30.5m	Boom	7,000kg	at 8.0m	( 4part-line)
8.0m	Jib	3,000kg	at 72 °	( 1part-line)
13.0m	Jib	2,000kg	at 76 °	( 1part-line)
Single top		3,500kg		( 1part-line)

### MAX.LIFTING HEIGHT

Boom	31.3m
Jib	44.2m

### MAX.WORKING RADIUS

Boom	28.0m
Jib	35.0m

### BOOM LENGTH

9.5m – 30.5m

### BOOM EXTENSION

21.0m

### BOOM EXTENSION SPEED

21.0m/90s

### JIB LENGTH

8.0m, 13.0m

### MAIN WINCH SINGLE LINE WINDING SPEED

120m/min (4th layer)

### MAIN WINCH HOOK SPEED

15.0m/min (8 part-line)

### AUXILIARY WINCH SINGLE LINE WINDING SPEED

120m/min (4th layer)

### AUXILIARY WINCH HOOK SPEED

120m/min (1 part-line)

### BOOM ELEVATION ANGLE

0 °– 83 °

### BOOM ELEVATION SPEED

0 °– 83 °/45s

### SWING ANGLE

360 °continue

### SWING SPEED

2.6min<sup>-1</sup> (rpm)

### WIRE ROPE

Main Winch

16mm x 170m (Diameter x Length)

Spin-resistant wire rope

Auxiliary Winch

16mm x 98m (Diameter x Length)

Spin-resistant wire rope

### BOOM

4-section hydraulically telescoping boom of hexagonal

box construction

(stage 2: sequential; stages 3,4: synchronized)

### BOOM EXTENSION

2 double-acting hydraulic cylinders

1 wire rope type telescoping device

### JIB

Quick-turn type (2-staged type which stores alongside below the base boom section and extendible from under the boom (with 2nd stage being a pull-out type))

Hydraulic non-stage offset (5 °– 45 °) type

### SINGLE TOP

Single sheave. Mounted on main boom head for single line work.

### HOIST

Driven by hydraulic motor and via spur gear reducer.

With free-fall device.

Automatic brake (with foot brake for free-fall device)

2 single winches

With flow regulator valve with pressure compensation

### BOOM ELEVATION

1 double-acting hydraulic cylinder

With flow regulator valve with pressure compensation

### SWING

Hydraulic motor driven planetary gear reducer

Swing bearing

Swing free/lock changeover type

Negative brake

### OUTRIGGERS

Fully hydraulic X-type (floats mounted integrally)

Slides and jacks each provided with independent operation device.

Fully extended width 6.3m

Middle extended width 5.9m, 5.0m, 3.6m

Minimum extended width 3.1m

### OPERATION METHOD

Hydraulic pilot valve operation

### MAX. VERTICAL LOAD CAPACITY OF OUTRIGGER

26.8t

### POWER TAKE-OFF

PTO wet multi-plate clutch

### HYDRAULIC PUMPS

2 variable piston pumps

2 gear pumps

### HYDRAULIC OIL TANK CAPACITY

380 liters

### SAFETY DEVICES

Automatic moment limiter (AML)

Swing automatic stop device

Elevation slow down and stop device

Over-winding cutout device

Working area control device

Free-fall interlock device

Outrigger extension width detector

Winch drum lock

Level gauge

Hook safety latch

Hydraulic safety valve

Telescopic counterbalance valve

Elevation counterbalance valve

Power tilt counterbalance valve

Jack pilot check valve

Swing lock

### EQUIPMENT

Air-conditioner with dehumidifier

Hydraulic oil temperature indication lamp

Radio

Oil cooler

Visual-type winch drum rotation indicator

Operation pedals

ISO arrangement: for telescoping/auxiliary hoisting

TADANO arrangement: for elevating/telescoping

Television (option)

## CARRIER SPECIFICATIONS

### ENGINE

Model MITSUBISHI 6M60 - TLE2A  
(with turbo charger and air cooler)  
Type 4-cycle, 6-cylinder, direct-injection, water-cooled  
diesel engine  
Piston displacement 7,545cc  
Max. output 200kW {272PS} at 2,700min<sup>-1</sup>{rpm}  
Max. torque 785N·m {80.0kgf·m} at 1,400min<sup>-1</sup>{rpm}

### TORQUE CONVERTER

3-element, 1-stage unit (with automatic lock-up  
mechanism)

### TRANSMISSION

Automatic and manual transmission  
Power shift type (wet multi-plate clutch)  
4 forward and 1 reverse speeds (with Hi/Low settings)

### REDUCER

Axle dual-ratio reduction

### DRIVE

2-wheel drive (4X2) / 4-wheel drive (4X4) selection

### FRONT AXLE

Full floating type

### REAR AXLE

Full floating type

### SUSPENSION

Front

Hydro-pneumatic suspension (with hydraulic lock cylinder)

Rear

Hydro-pneumatic suspension (with hydraulic lock cylinder)

### STEERING

Fully hydraulic power steering  
With reverse steering correction mechanism

### BRAKE SYSTEM

Service Brake

Hydro-pneumatic disk brake

Parking Brake

Mechanically operated, internal expanding duo-servo  
shoe type acting on drum at transmission case rear.

Auxiliary Brake

Hydrodynamic retarder

Electro-pneumatic operated exhaust brake

Auxiliary braking device for operations

### FRAME

Welded box-shaped structure

### ELECTRIC SYSTEM

12 V DC. 2 batteries of 24V (120Ah)

### FUEL TANK CAPACITY

300 liters

### TIRES

Front 385/95R25 170E ROAD

Rear 385/95R25 170E ROAD

### CAB

One-man type

With interior equipment

Liquid filled rubber mounted type

Fully adjustable foldable seat

(with headrest, armrest and seat belt)

Adjustable handle (tilt, telescoping)

Intermittent type windshield/roof wiper (with washer)

Power window

Side visor

### SAFETY DEVICES

Emergency steering device

Suspension lock device

Rear wheel steering lock device

Engine over-run alarm

Overshift prevention device

Parking brake alarm

Powered mirror for right side of boom

Monitor TV for left side of boom

### EQUIPMENT

Centralized oiling device

Electric mirror

## GENERAL DATA

### DIMENSIONS

Overall length	11,130mm
Overall width	2,620mm
Overall height	3,455mm
Wheel base	3,500mm
Tread Front	2,170mm
Rear	2,170mm

### WEIGHTS

Gross vehicle weight	
Total	26,495kg
Front	13,250kg
Rear	13,245kg

### PERFORMANCE

Max. traveling speed	49km/h
Gradeability (tan )	0.57
Min. turning radius	5.0m (4-wheel steering)
	8.4m (2-wheel steering)

Note:

This crane is covered by Class C Conditions under the  
Basic Running Conditions of the Road Traffic Act.

<b>TOTAL RATED LOADS</b>
--------------------------

(1) With outriggers set  
[BOOM]

Unit:ton

Outriggers fully extended (6.3m) –360 °–				
A B	9.5m	16.5m	23.5m	30.5m
2.5m	25.0	19.0	12.5	
3.0m	25.0	19.0	12.5	
3.5m	25.0	19.0	12.5	7.0
4.0m	23.0	19.0	12.5	7.0
4.5m	21.2	18.0	12.5	7.0
5.0m	19.4	16.7	12.5	7.0
5.5m	17.8	15.6	11.85	7.0
6.0m	16.3	14.6	11.2	7.0
6.5m	15.1	13.8	10.6	7.0
7.0m	13.7	13.0	10.1	7.0
8.0m		10.55	9.1	7.0
9.0m		8.5	8.2	6.4
10.0m		7.05	7.4	5.9
11.0m		5.85	6.4	5.35
12.0m		4.95	5.5	4.9
13.0m		4.2	4.75	4.5
14.0m		3.6	4.1	4.15
15.0m			3.6	3.85
16.0m			3.15	3.45
17.0m			2.8	3.05
18.0m			2.45	2.7
19.0m			2.15	2.45
20.0m			1.9	2.2
21.0m			1.7	1.95
22.0m				1.75
24.0m				1.4
26.0m				1.15
28.0m				0.95
a (°)	0 ~ 83			

Unit:ton

Outriggers middle extended (5.9m) –Over sides–				
A B	9.5m	16.5m	23.5m	30.5m
2.5m	25.0	19.0	12.5	
3.0m	25.0	19.0	12.5	
3.5m	25.0	19.0	12.5	7.0
4.0m	23.0	19.0	12.5	7.0
4.5m	21.2	18.0	12.5	7.0
5.0m	19.4	16.7	12.5	7.0
5.5m	17.8	15.6	11.85	7.0
6.0m	16.3	14.6	11.2	7.0
6.5m	15.1	13.8	10.6	7.0
7.0m	13.0	12.6	10.1	7.0
8.0m		9.7	9.1	7.0
9.0m		7.7	8.2	6.4
10.0m		6.3	7.0	5.9
11.0m		5.2	6.0	5.35
12.0m		4.35	5.1	4.9
13.0m		3.7	4.35	4.5
14.0m		3.15	3.8	4.05
15.0m			3.3	3.6
16.0m			2.85	3.15
17.0m			2.5	2.75
18.0m			2.2	2.45
19.0m			1.95	2.2
20.0m			1.7	1.95
21.0m			1.5	1.75
22.0m				1.55
24.0m				1.2
26.0m				0.95
27.9m				0.75
a (°)	0 ~ 83			

A= Boom length B= Working radius

a= Boom angle range (for the unladen condition)

## [BOOM]

Unit:ton

Outriggers middle extended (5.0m) –Over sides–				
$\begin{array}{c} A \\ \diagdown \\ B \end{array}$	9.5m	16.5m	23.5m	30.5m
2.5m	25.0	19.0	12.5	
3.0m	25.0	19.0	12.5	
3.5m	25.0	19.0	12.5	7.0
4.0m	23.0	19.0	12.5	7.0
4.5m	21.2	18.0	12.5	7.0
5.0m	18.4	16.7	12.5	7.0
5.5m	15.4	15.0	11.85	7.0
6.0m	13.0	12.6	11.2	7.0
6.5m	11.2	10.8	10.6	7.0
7.0m	9.5	9.4	10.1	7.0
8.0m		7.3	8.0	7.0
9.0m		5.85	6.5	6.4
10.0m		4.75	5.4	5.6
11.0m		3.9	4.55	4.8
12.0m		3.3	3.85	4.15
13.0m		2.75	3.3	3.55
14.0m		2.3	2.85	3.1
15.0m			2.45	2.7
16.0m			2.1	2.35
17.0m			1.8	2.1
18.0m			1.55	1.8
19.0m			1.35	1.6
20.0m			1.15	1.4
21.0m			0.95	1.2
22.0m				1.05
24.0m				0.75
26.0m				0.5
a (°)	0~83			20~83

Unit:ton

Outriggers middle extended (3.6m) –Over sides–				
$\begin{array}{c} A \\ \diagdown \\ B \end{array}$	9.5m	16.5m	23.5m	30.5m
2.5m	25.0	19.0	12.5	
3.0m	25.0	19.0	12.5	
3.5m	20.5	19.0	12.5	7.0
4.0m	16.0	15.7	12.5	7.0
4.5m	12.8	12.6	12.5	7.0
5.0m	10.7	10.5	11.0	7.0
5.5m	9.05	8.8	9.4	7.0
6.0m	7.7	7.6	8.2	7.0
6.5m	6.6	6.5	7.25	7.0
7.0m	5.8	5.6	6.4	6.5
8.0m		4.4	5.05	5.3
9.0m		3.4	4.05	4.35
10.0m		2.7	3.3	3.65
11.0m		2.15	2.75	3.05
12.0m		1.7	2.3	2.6
13.0m		1.3	1.9	2.2
14.0m		1.0	1.6	1.85
15.0m			1.3	1.55
16.0m			1.05	1.3
17.0m			0.85	1.05
18.0m			0.65	0.9
19.0m			0.5	0.7
20.0m				0.55
a (°)	0~83		20~83	42~83

A= Boom length B= Working radius

a= Boom angle range (for the unladen condition)

## [BOOM]

Unit:ton

Outriggers minimum extended (3.1m) –Over sides–				
A B	9.5m	16.5m	23.5m	30.5m
2.5m	18.0	14.2	12.2	
3.0m	18.0	14.2	12.2	
3.5m	14.5	14.2	12.2	7.0
4.0m	11.6	11.25	12.2	7.0
4.5m	9.5	9.15	10.05	7.0
5.0m	7.9	7.65	8.45	7.0
5.5m	6.75	6.45	7.25	7.0
6.0m	5.75	5.5	6.25	6.5
6.5m	5.0	4.75	5.45	5.7
7.0m	4.25	4.1	4.8	5.0
8.0m		3.0	3.8	4.0
9.0m		2.2	3.0	3.2
10.0m		1.6	2.4	2.6
11.0m		1.1	1.9	2.1
12.0m		0.7	1.5	1.7
13.0m			1.1	1.4
14.0m			0.8	1.1
15.0m				0.8
16.0m				0.6
a ( ° )	0 ~ 83	21 ~ 83	40 ~ 83	54 ~ 83

A= Boom length B= Working radius

a= Boom angle range (for the unladen condition)

[JIB]

Unit:ton

Outriggers fully extended (6.3m)												-360 °-
C D E ( ° )	30.5m Boom + 8.0m Jib						30.5m Boom + 13.0m Jib					
	5 °		25 °		45 °		5 °		25 °		45 °	
	B (m)	M	B (m)	M	B (m)	M	B (m)	M	B (m)	M	B (m)	M
83	4.3	3.0	6.9	2.1	8.9	1.6	5.7	2.0	10.0	1.2	13.0	0.8
76	9.5	3.0	11.8	2.1	13.5	1.6	11.7	2.0	15.5	1.2	18.1	0.8
72	12.3	3.0	14.4	2.1	15.9	1.6	14.6	1.75	18.4	1.1	20.5	0.8
70	13.6	2.8	15.6	2.1	17.0	1.6	16.1	1.65	19.7	1.05	21.8	0.8
65	16.6	2.35	18.5	1.8	19.7	1.5	19.6	1.4	22.8	0.95	24.5	0.78
60	19.6	2.0	21.2	1.55	22.1	1.35	22.8	1.2	25.8	0.9	27.0	0.75
55	22.2	1.45	23.7	1.35	24.4	1.2	25.9	1.05	28.5	0.85	29.4	0.74
50	24.6	1.05	26.0	1.0	26.5	0.95	28.6	0.85	31.0	0.75	31.5	0.7
45	26.9	0.75	28.1	0.7	28.3	0.7	31.1	0.6	33.1	0.55	33.3	0.55
40	29.0	0.55	29.9	0.5			33.3	0.4	35.0	0.4		
35	30.8	0.38	31.6	0.35								
a ( ° )	34 ~ 83				44 ~ 83		39 ~ 83				44 ~ 83	

Unit:ton

Outriggers middle extended (5.9m)												-Over sides-
C D E ( ° )	30.5m Boom + 8.0m Jib						30.5m Boom + 13.0m Jib					
	5 °		25 °		45 °		5 °		25 °		45 °	
	B (m)	M	B (m)	M	B (m)	M	B (m)	M	B (m)	M	B (m)	M
83	4.3	3.0	6.9	2.1	8.9	1.6	5.7	2.0	10.0	1.2	13.0	0.8
76	9.5	3.0	11.8	2.1	13.5	1.6	11.7	2.0	15.5	1.2	18.1	0.8
72	12.3	3.0	14.4	2.1	15.9	1.6	14.6	1.75	18.4	1.1	20.5	0.8
70	13.6	2.8	15.6	2.1	17.0	1.6	16.1	1.65	19.7	1.05	21.8	0.8
65	16.6	2.35	18.5	1.8	19.7	1.5	19.6	1.4	22.8	0.95	24.5	0.78
60	19.5	1.85	21.2	1.55	22.1	1.35	22.8	1.2	25.8	0.9	27.0	0.75
55	22.1	1.3	23.7	1.15	24.4	1.1	25.9	1.05	28.5	0.85	29.4	0.74
50	24.5	0.9	25.9	0.85	26.5	0.8	28.6	0.7	30.9	0.6	31.5	0.6
45	26.8	0.6	28.0	0.55	28.3	0.55	31.0	0.5	33.0	0.4	33.3	0.4
40	28.9	0.4	29.9	0.35			33.3	0.3				
a ( ° )	39 ~ 83				44 ~ 83		39 ~ 83		44 ~ 83			

B= Working radius C= Jib length D= Jib offset  
E= Boom angle M= Total rated loads  
a= Boom angle range (for the unladen condition)



[JIB]

Unit:ton

Outriggers middle extended (5.0m) –Over sides–												
C D E ( ° )	30.5m Boom + 8.0m Jib						30.5m Boom + 13.0m Jib					
	5 °		25 °		45 °		5 °		25 °		45 °	
	B (m)	M	B (m)	M	B (m)	M	B (m)	M	B (m)	M	B (m)	M
83	4.3	3.0	6.9	2.1	8.9	1.6	5.7	2.0	10.0	1.2	13.0	0.8
76	9.5	3.0	11.8	2.1	13.5	1.6	11.7	2.0	15.5	1.2	18.1	0.8
72	12.3	3.0	14.4	2.1	15.9	1.6	14.6	1.75	18.4	1.1	20.5	0.8
70	13.6	2.8	15.6	2.1	17.0	1.6	16.1	1.65	19.7	1.05	21.8	0.8
65	16.5	2.0	18.5	1.7	19.7	1.5	19.6	1.4	22.8	0.95	24.5	0.78
60	19.3	1.3	21.0	1.15	22.1	1.1	22.7	1.0	25.8	0.9	27.0	0.75
55	21.8	0.8	23.5	0.75	24.3	0.75	25.7	0.65	28.4	0.6	29.4	0.5
50	24.3	0.5	25.8	0.45	26.4	0.45	28.3	0.4	30.8	0.35	31.4	0.3
a ( ° )	49 ~ 83						49 ~ 83					

Unit:ton

Outriggers minimum extended (3.6m) –Over sides–												
C D E ( ° )	30.5m Boom + 8.0m Jib						30.5m Boom + 13.0m Jib					
	5 °		25 °		45 °		5 °		25 °		45 °	
	B (m)	M	B (m)	M	B (m)	M	B (m)	M	B (m)	M	B (m)	M
83	4.4	3.0	6.9	2.1	8.9	1.6	5.7	2.0	10.0	1.2	13.0	0.8
76	9.5	3.0	11.8	2.1	13.5	1.6	11.7	2.0	15.5	1.2	18.1	0.8
72	12.0	2.2	14.3	1.8	15.9	1.6	14.6	1.75	18.4	1.1	20.5	0.8
70	13.2	1.8	15.4	1.5	16.9	1.35	15.9	1.4	19.7	1.05	21.8	0.8
65	16.1	1.0	18.1	0.9	19.4	0.8	19.1	0.8	22.6	0.65	24.4	0.55
60	18.9	0.5	20.7	0.45	21.8	0.4	22.2	0.4	25.3	0.35	26.8	0.3
a ( ° )	59 ~ 83						59 ~ 83					

B= Working radius C= Jib length D= Jib offset  
E= Boom angle M= Total rated loads  
a= Boom angle range (for the unladen condition)

**PRECAUTIONS TO BE TAKEN WHEN THE OUTRIGGERS ARE EXTENDED:**

1. The total rated loads shown are for the case where the crane is set horizontally on firm level ground. They include the weights of the slings and hooks (main hook: 260kg, 12t hook: 170kg, auxiliary hook: 60kg).  
The values above the bold lines are based on the crane strength while those below are based on the crane stability.
2. Since the working radii are based on the actual values including the deflection of the boom, operations should be performed in accordance with the working radii.
3. Jib operations should be performed in accordance with the boom angle, irrespective of the boom length. The working radii are reference values for the case where the jib is mounted on a 30.5m boom.
4. The total rated load for the single top shall be the value obtained by subtracting the weight of the hook mounted on the boom from the total rated load of the boom and must not exceed 3.5t.
5. As a rule, free-fall operation should be performed only when lowering the hook alone. If a hoisted load must be lowered by free-fall operation, the load must be kept below 1/5th of the total rated load and sudden braking operations must be avoided.
6. The table below shows the standard number of part lines for each boom length. When using with other than this number of part lines, the load per line should not exceed 3.17t for the main winch, and 3.5t for the auxiliary winch..


A	9.5m	16.5m	23.5m	30.5m	J
H	8	6	4	4	1

A= Boom length H= No. of part-lines

J= Jib/Single top

7. The hoisting performance for the "Over sides" range will differ according to the extended width of the outriggers. Operations should be performed in accordance with the performance corresponding to the extended width. Also, although the hoisting performances for the "Over front" and "Over rear" ranges are equivalent to those of the "outriggers fully extended" condition, the front and rear ranges (angle  $\alpha$ ) will differ according to the width to which the outriggers are extended in the left and right directions.

Extended width	Middle extended (5.9m)	Middle extended (5.0m)	Middle extended (3.6m)	Minimum extended (3.1m)
Angle $\alpha$ °	35	25	15	5



## (2) Without outriggers

Unit:ton

B (m)	Stationary						Creep (travelling at 1.6km/h or less)					
	9.5m Boom		16.5m Boom		23.5m Boom		9.5m Boom		16.5m Boom		23.5m Boom	
	K	G	K	G	K	G	K	G	K	G	K	G
3.0	14.0	9.0	9.0	7.3			10.5	7.0	7.5	5.1		
3.5	14.0	7.6	9.0	7.3	6.5	4.5	10.5	6.2	7.5	5.1	5.5	3.2
4.0	12.5	6.3	9.0	5.85	6.5	4.5	9.5	5.3	7.5	4.9	5.5	3.2
4.5	10.9	5.2	9.0	4.75	6.5	4.5	8.7	4.4	7.5	3.95	5.5	3.2
5.0	9.55	4.3	8.2	4.0	6.5	4.3	8.0	3.6	7.0	3.3	5.5	3.2
5.5	8.3	3.6	7.4	3.3	6.1	3.7	6.9	3.0	6.2	2.7	5.15	3.1
6.0	7.2	3.0	6.6	2.8	5.65	3.2	5.9	2.5	5.5	2.3	4.8	2.7
6.5	6.25	2.5	5.9	2.35	5.25	2.75	5.1	2.1	4.9	1.9	4.45	2.3
7.0	5.2	2.0	5.25	1.95	4.85	2.4	4.3	1.7	4.35	1.6	4.15	2.0
8.0			4.1	1.4	4.1	1.8			3.4	1.1	3.5	1.5
9.0			3.25	0.95	3.5	1.4			2.7	0.7	2.95	1.1
10.0			2.6	0.6	3.0	1.05			2.15		2.45	0.8
11.0			2.1		2.55	0.75			1.7		2.05	0.6
12.0			1.7		2.2				1.35		1.7	
13.0			1.35		1.85				1.1		1.45	
14.0			1.0		1.55				0.8		1.2	
15.0					1.3						1.0	
16.0					1.05						0.85	
17.0					0.85						0.7	
18.0					0.65						0.55	
19.0					0.5							
a (°)	0 ~ 77		42 ~ 77	26 ~ 77	56 ~ 77		0 ~ 77		48 ~ 77	31 ~ 77	57 ~ 77	

B= Working radius K= Front G= 360 °

a= Boom angle range (for the unladen condition)

**PRECAUTIONS TO BE TAKEN WHEN THE OUTRIGGERS ARE NOT MOUNTED:**


1. The total rated loads shown are for the case where the tire air pressure on firm level ground is as specified (900kPa {9.00kgf/cm<sup>2</sup>}) and the suspension-lock cylinder is retracted as much as possible. They include the weights of the slings and hooks (main hook: 260kg, 12t hook: 170kg, auxiliary hook: 60kg). The values above the bold lines are based on the crane strength while those below are based on the crane stability. The foundation, working conditions, etc. should be taken into consideration for actual work.
2. Since the working radii are based on the actual values including the deflection of the boom and the tires, operations should be performed in accordance with the working radii.
3. The table below shows the standard number of part lines for each boom length. When using with other than this number of part lines, the load per line should not exceed 3.17t for the main winch, and 3.5t for the auxiliary winch.

A	9.5m	16.5m	23.5m	Single top
H	6	4	4	1

A= Boom length H= No. of part-lines

4. "Over front" crane operations should be performed only when the AML "over-front area indicator lamp" is lit. The boom must be kept inside a 2° area over front of the carrier when performing "Over front" crane operations without the outriggers.
5. The total rated load for the single top shall be the value obtained by subtracting the weight of the hook mounted on


Approx. 2°



the boom from the total rated load of the boom and must not exceed 3.5t.

6. Free-fall operations should not be performed without outriggers. Booms over 23.5m in length and jibs should not be used without outriggers.
7. The "Drive Mode Selection" switch should be set to "4-wheel / Lo" for creeping while hoisting a load and the shift lever should be set to first.
8. When creeping while hoisting a load, the swing brake should be applied, the load should be kept as close to the ground as possible but not touching the ground and the speed should be kept at 1.6km/h or less. In particular, any abrupt steering, starting or braking must be avoided.
9. Crane operations should not be performed when creeping while hoisting a load.


# WORKING RADIUS - LIFTING HEIGHT



## NOTES:

1. The deflection of the boom is not incorporated in the figure above.
2. The figure above is for the case where the outriggers are fully extended (360°).

DIMENSIONS (1/100)



# MEMO

[illegible]